RKARV-300



3" Aluminum Air Vent



Technical Specifications


- Minimum Sealing Pressure: 7 10 PSI
- Working Pressure Range: 7 100 PSI

Features

- Large volume air release as line is filled
- Positive vacuum relief when line is draining
- Does not leak at low pressure
- Venting passage protected by cover

Functions

- Expulsion (Kinetic Air): When the pipe is being filled, the air release valve remains open, expelling the surplus air
- When the pipe is not full of water, air release valve closes tightly
- Air Admission (Air Intake): While negative pressure (pipe vaccuum) the air release valve opens to allow the air to go inside the pipe
- This system avoids possible damages in pipes and accessories



IrrigationKing.com | 9995 SW Avery St, Tualatin, OR 97062 | (844) 259-0640 | support@irrigationking.com

IrrigationKing product specifications in U.S. customary units and metric are approximate and are provided for reference only. For precise measurements, please contact IrrigationKing. IrrigationKing reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on IrrigationKing products previously or subsequently sold.

Dimensions

Size		Nominal	Clear Opening Diameter	Height	Width	Weight (lbs)
1"	in.	1	0.67	4.2	2.2	0.55
	mm.	25.4	17	106.5	55	
1½"	in.	1½	1.16	4.9	3.2	1.16
	mm.	38.1	29.5	123.5	82.5	
2"	in.	2	1.89	5.7	3.5	1.65
	mm.	50.8	48	145.5	88	
3"	in.	3	2.54	7.9	4.9	3.63
	mm.	76.2	64.5	200	124	
4"	in.	4	3.43	9.7	7.1	6.72
	mm.	101.6	87	247.5	180.5	