



PRODUCT SPECIFICATION SHEET | **SKU RKPG-3**

Glycerine Filled Pressure Gauge – 0-30 PSI, 2-1/2" Stainless Steel, 1/4" MPT



SPECIFICATIONS

Pressure Range	0-30 PSI
Dial Size	2-1/2"
Body Material	Stainless Steel
Connection	1/4" MPT (bottom mount)
Fill	Glycerine
Temperature Range	-40°F to 140°F

Glycerine filled pressure gauge with a 0-30 PSI range – the glycerine fill dampens vibrations and pulsations for a steady, easy-to-read dial even on systems with pumps, valves, or pressure regulators. 2-1/2" stainless steel body resists corrosion in outdoor agricultural environments.

Operates from -40°F to 140°F. 1/4" MPT connection threads into standard pressure test ports, tees, and filter housings. Ideal for low-pressure drip and micro-irrigation systems.

FEATURES

- Glycerine filled – dampens vibrations and pulsations for a stable, easy-to-read dial; also lubricates internal components for longer gauge life
- 2-1/2" stainless steel body – corrosion-resistant and durable for outdoor installation in agricultural environments
- 0-30 PSI range – suited for low-pressure drip and micro-irrigation systems
- 1/4" MPT connection – threads into standard pressure test ports, tees, filter housings, and pressure regulator ports
- Wide temperature range (-40°F to 140°F) – operates reliably in extreme cold and heat